

Your pool comprises

- 4 pipes of 100 cm (for the laterals)
- 4 pipes of 33 cm (for support-structure)
- 4 plastic curves (for the 4 corners)
- 4 plastic pointers
- 1 valve cap
- 1 extra repair-kit
- 1 swimming-pool PVC canvas *400 liters

1. Fit the plastic pointers onto tubes of 33 cm (legs).
2. Place the bigger tubes (100 cm) into each opening of the lateral border.
3. Place a curved joint on each corner of your swimming-pool fitting it into the tubes.
4. Fit tubes into each of the 4 curves (at this point keep joints uncovered so as not to tear the PVC canvas).
5. Lower the canvas's borders on all corners to cover the curves.
6. Place the cap of the escape valve on the printed, inner side of the pool.




Fig. 1

Emptying

1. Use the water escape valve located in one of the swimming-pool corners.
2. Never empty the swimming-pool by lifting one of the corners or one of the extremes.

Conservation

1. Avoid dragging swimming-pool from one place to another.
2. Clean chosen area avoiding sharp or cutting objects.
3. Give preference to flat and smooth surfaces and utilize a lining sheet for better protection.
4. Never store PVC canvas when wet, or in humid places.
5. Water must be changed every second day – to use same water longer we recommend following the product manufacturer's instructions. We suggest this site as a basis for research: www.genco.com.br




Fig. 2

Useful tips

After water treatment is done, wait for at least 2 hours before using swimming pool.

Caution

1. Assemblage of swimming-pool must be done by adults.
2. Adult supervision is essential when children are using the swimming-pool.
3. No sharp, cutting objects and electrical equipment are to be used in the pool.
4. Never sit on the edges of the swimming-pool.
5. Never support yourself on the structure of the swimming-pool to jump.

Repairs

If there is eventual damage of sheet, clean the area around the hole – on the printed side – cut a piece of extra material and spread a special bonder for flexible PVC (this glue can be found in hardware store and in magazines). For good adherence keep pressure on the spot for 5 minutes. Wait 2 hours before utilizing PVC canvas.